

# Daikin Altherma low temperature split

EHVH-CB



Guaranteed  
operation  
down to -25°C

Floor standing air to water heat pump for heating and hot water, ideal for low energy houses

- › Perfect fit for new built as well as for low energy houses
- › Best seasonal efficiencies, providing the highest savings on running costs
- › Integrated indoor unit: all-in-one floor standing unit including the domestic hot water tank
- › Energy efficient heating only system based on air to water heat pump technology
- › Flexible configuration with respect to heat emitters
- › Outdoor unit extracts heat from the outdoor air, even at -25°C

# EHVH-CB + ERLQ-CV3/CW1





Efficiency data		EHVH + ERLQ	04S18CB3V + 004CV3	08S18CB3V / 08S26CB9W + 006CV3	08S18CB3V / 08S26CB9W + 008CV3	11S18CB3V / 11S26CB9W + 011CV3	16S18CB3V / 16S26CB9W + 014CV3	16S18CB3V / 16S26CB9W + 016CV3	11S18CB3V / 11S26CB9W + 011CW1	16S18CB3V / 16S26CB9W + 014CW1	16S18CB3V / 16S26CB9W + 016CW1	
Heating capacity	Min.	kW	1.80 (1) / 1.80 (2)									
	Nom.	kW	4.40 (1) / 4.03 (2)	6.00 (1) / 5.67 (2)	7.40 (1) / 6.89 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)	
	Max.	kW	5.12 (1) / 4.90 (2)	8.35 (1) / 7.95 (2)	10.02 (1) / 9.53 (2)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)	
Power input	Heating	Nom.	kW	0.87 (1) / 1.13 (2)	1.27 (1) / 1.59 (2)	1.66 (1) / 2.01 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)
		Max.	kW	-			3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)	3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)
Nominal efficiency COP				5.04 (1) / 3.58 (2)	4.74 (1) / 3.56 (2)	4.45 (1) / 3.42 (2)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)

Indoor unit		EHVH	04S18CB3V	08S18CB3V / 08S26CB9W	11S18CB3V / 11S26CB9W	16S18CB3V / 16S26CB9W	11S18CB3V / 11S26CB9W	16S18CB3V / 16S26CB9W	
Casing	Colour	White							
	Material	Precoated sheet metal							
Dimensions	Unit	HeightxWidthxDepth	mm						
			1,732x600x728						
Weight	Unit	kg	116	117/126	117/126	118/127	117/126	118/127	
Tank	Water volume	l	180	180/260					
	Insulation Heat loss	kWh/24h	1.4	1.4/1.9					
	Corrosion protection		Anode						
Sound power level	Cooling	dBA	42			-			
Sound pressure level	Cooling	Nom.	dBA	28			-		

Outdoor unit		ERLQ	004CV3	006CV3	008CV3	011CV3	014CV3	016CV3	011CW1	014CW1	016CW1	
Dimensions	Unit	HeightxWidthxDepth	mm				1,345x900x320					
Weight	Unit	kg	54	56		113			114			
Operation range	Heating	Ambient	Min.-Max.	°CDB			-25~25			-25~35		
	Domestic hot water	Ambient	Min.-Max.	°CWB			-25~35			-20~35		
Refrigerant	Type / GWP	R-410A / 2,087.5										
	Charge	kg/ TCO <sub>2</sub> Eq	1.45/ 3.0	1.6/ 3.3		3.4/ 7.1						
Sound power level	Heating	dBA	61	62		64	66		64	66		
Sound pressure level	Heating	Nom.	dBA	48	49		51	52		51	52	
Power supply	Phase / Frequency / Voltage	Hz / V	V3/1~/50/230						W1/3N~/50/400			
Current - 50Hz	Maximum fuse amps (MFA)	A	20			40			20			

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) (3) Condition 3: heating Ta DB -7°C (RH85%) - LWC 35°C (4) Condition 4: heating Ta DB -7°C (RH85%) - LWC 45°C | Contains fluorinated greenhouse gases

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-756 04/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.